

FORM PTO-1390 (Modified)
(REV 10-95)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

0524-3264-0 PCT

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09 / 509548

INTERNATIONAL APPLICATION NO.
PCT/EP98/06527INTERNATIONAL FILING DATE
14 October 1998PRIORITY DATE CLAIMED
15 October 1997

TITLE OF INVENTION

HEAT-INSULATING COATING

APPLICANT(S) FOR DO/EO/US

Karl SIEMENSMEYER, et al.

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210).
8. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
11. ☐ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 13 to 18 below concern document(s) or information included:

13. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
A **SECOND** or **SUBSEQUENT** preliminary amendment.
16. ☐ A substitute specification.
17. ☐ A change of power of attorney and/or address letter.
18. ☐ Certificate of Mailing by Express Mail
19. ☒ Other items or information:

Request for Consideration of Documents Cited in International Search Report

Notice of Priority

PCT/IB/304

PCT/IB/308

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/509548

INTERNATIONAL APPLICATION NO.

PCT/EP98/06527

ATTORNEY'S DOCKET NUMBER

0524-3264-0 PCT

20. The following fees are submitted:

CALCULATIONS PTO USE ONLY

BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :

- ☒ Search Report has been prepared by the EPO or JPO **\$840.00**
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) **\$670.00**
- ☐ No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) **\$760.00**
- ☐ Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO **\$970.00**
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) **\$96.00**

ENTER APPROPRIATE BASIC FEE AMOUNT =**\$840.00**

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

\$0.00

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	14 - 20 =	0	x \$18.00
Independent claims	1 - 3 =	0	x \$78.00

\$0.00**\$0.00**Multiple Dependent Claims (check if applicable). ☐**\$0.00****TOTAL OF ABOVE CALCULATIONS =****\$840.00**

Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). ☐

\$0.00**SUBTOTAL =****\$840.00**

Processing fee of **\$130.00** for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).

\$0.00**TOTAL NATIONAL FEE =****\$840.00**

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). ☐

\$0.00**TOTAL FEES ENCLOSED =****\$840.00****Amount to be: refunded**

\$

charged

\$

☒ A check in the amount of **\$840.00** to cover the above fees is enclosed.

☐ Please charge my Deposit Account No. _____ in the amount of _____ to cover the above fees.
A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **15-0030** A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

OBLON, SPIVAK, McCLELLAND, MAIER & NEUSTADT, P.C.
Crystal Square Five, Fourth Floor
1755 Jefferson Davis Highway
Arlington, Virginia 22202
703-413-3000

WILLIAM E. BEAUMONT
REGISTRATION NUMBER 30,996

SIGNATURE

Norman F. Oblon

NAME

24,618

REGISTRATION NUMBER

DATE

April 12, 2000

09/509548

422 Rec'd PCT/PTO 12 APR 2000

Docket No. 0524-3264-0 PCT

IN THE UNITED STATES PATENT & TRADEMARK OFFICE

IN RE APPLICATION OF :
KARL SIEMENSMEYER ET AL : ATTN: APPLICATION DIVISION
SERIAL NO: NEW APPLICATION :
(Based on PCT NO:EP98/06527)
FILED: HEREWITH :
FOR: HEAT-INSULATING COATING :

PRELIMINARY AMENDMENT

ASSISTANT COMMISSIONER FOR PATENTS
WASHINGTON, D.C. 20231

SIR:

Prior to examination on the merits, please amend the above-identified application as follows.

IN THE CLAIMS

Please cancel Claims 1-13.

Please add the following claims:

--14. A heat-insulating coating comprising one or more non-micellar cholesteric layers and reflecting at least 40% of the incident radiation in the infrared wavelength range above 750 nm.

15. A heat-insulating coating as claimed in claim 14, which transmits at least 80% of the incident radiation in the wavelength range from about 390 nm to 750 nm.

16. A heat-insulating coating as claimed in claim 14, which comprises two or more cholesteric IR-reflecting layers.

17. A heat-insulating coating as claimed in claim 16, whose cholesteric layers have mutually different reflection maxima in the wavelength range > 750 nm.

18. A heat-insulating coating as claimed in claim 14, which comprises two or more cholesteric layers, the pitch of the helical superstructures of 2 layers in each case being identical but their handedness being different.

19. A heat-insulating coating as claimed in claim 14, which between layers having a helical superstructure of identical pitch and identical handedness has a medium which reverses the direction of rotation of the transmitted circularly polarized light.

20. A heat-insulating coating as claimed in claim 19, which reflects at least 75% of the incident radiation in the wavelength range above 750 nm.

21. A heat-insulating coating as claimed in claim 14, which in the cured state comprises cholesteric compounds or mixtures of compounds selected from

- a) at least one cholesteric polymerizable monomer;
- b) at least one achiral, nematic, polymerizable monomer and a chiral compound;
- c) at least one cholesteric crosslinkable polymer;
- d) at least one cholesteric polymer in a polymerizable diluent or a mixture of polymerizable diluents;
- e) at least one cholesteric polymer whose cholesteric phase can be frozen in by rapid cooling to below the glass transition temperature; or
- f) at least one achiral, liquid-crystalline crosslinkable polymer and a chiral compound.

22. A process for producing a heat-insulating coating as claimed in claim 14, which comprises applying to a transparent substrate at least one cholesteric IR-reflecting layer, curing it, applying, if desired, one or more further cholesteric IR-reflecting layers and, if

desired, a medium which reverses the direction of rotation of the transmitted circularly polarized light, curing said layer(s) and so completing the heat-insulating coating.

23. A multicomponent coating system, comprising components capable of forming cholesteric layers in accordance with the definition in any of claim 17.

24. A heat-insulating coating as claimed in claim 14 for producing insulating windows or heat-insulating transparent construction materials or for insulating residential, office or industrial buildings.

25. A heat-insulating coating as claimed in claim 14 for use in the automotive sector, especially for producing heat-insulating laminated glass screens.

26. A film, comprising a heat-insulating coating as claimed in claim 14.

27. The film as claimed in claim 26, which is an adhesive film.--

REMARKS

Claims 14-27 are active in this application.


Newly added Claims 14-27 are supported by the specification at pages 3-44 and by original Claims 1-13. No new matter is believed to have been added to this application by these amendments.

Applicants submit that the present application is ready for examination on the merits.

Early notice to this effect is earnestly solicited.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,
MAIER & NEUSTADT, P.C.



Norman F. Oblon
Attorney of Record
Registration No. 24,618

James J. Kelly, Ph.D.
Registration No. 41,504

Crystal Square Five - Fourth Floor
1755 Jefferson Davis Highway
Arlington, VA 22202
(703) 413-3000
Fax #: (703) 413-2220
JK/NFO/rac

I:\atty\JK\05243264.PR

WILLIAM E. BEAUMONT
REGISTRATION NUMBER 30,996

Heat-insulating coating

- 5 The invention relates to a heat-insulating coating which comprises one or more cholesteric IR-reflecting layers.

10 The problem of screening against thermal radiation is important in particular in connection with the insulation of residential, office or industrial buildings. Buildings with a generous expanse of windows heat up rapidly, especially in summer and in southerly regions in particular, to such an extent that they have to be cooled at considerable energy cost by air conditioning units.

- 15 Common techniques of heat insulation, especially for screening against thermal radiation in the wavelength range between 800 nm and 2000 nm, are based on the absorption of the radiation by appropriate dyes or pigments. However, a large part of the energy absorbed is passed on by conduction to the area or item which is
20 to be insulated.

The use of materials which substantially reflect thermal radiation is also known.

- 25 For this purpose there is widespread use of special dyes or pigments, but also graphite or gold, as broadband absorbers or reflectors.
- 30 Examples of dyes employed in this context are naphthalocyanines having broadband absorption in the infrared (IR), or else laked polymethine dyes. However, a serious disadvantage of the IR-absorbing dyes is that they exhibit marked absorption in the visible wavelength range as well, with the result that a
35 considerable reduction in transparency is observed. The radiative energy absorbed is transformed into thermal energy which is dissipated by conduction.

- Graphite, gold, silver or indium-tin oxide (ITO), which are also
40 employed as absorbers or reflectors for IR radiation, have comparable disadvantages. Here too, especially in the visible region of the spectrum, there is very little transparency. Only highly precise and hence extensive production of extremely thin layers ensures a sufficiently uniform and high level of
45 transmission in the visible wavelength range. Metal layers of

this kind are generally applied by chemical or physical vapor deposition techniques (CVD or PVD), which are highly complex.

It is likewise known that cholesteric liquid-crystalline substances are also able to reflect light in the IR region of the electromagnetic spectrum. Cholesteric (chiral nematic) liquid crystals have already long been known. The first example of such a material was discovered by the Austrian botanist F. Reinitzer (Monatshefte Chemie, 9 (1888), 421). It is the chirality which determines the existence of cholesteric phases. The chiral moiety can either be present in the liquid-crystalline molecule itself or can be added as a dopant to the nematic phase, thereby inducing the chiral nematic phase. The chiral nematic phase has special optical properties: a high optical rotation and a pronounced circular dichroism resulting from selective reflection of circularly polarized light within the nematic layer. A consequence of this is that not more than 50% of the incident light having the reflection wavelength is reflected. The remainder passes through without interacting with the medium. The direction of rotation of the reflected light is determined by the handedness of the helix: a right-handed helix reflects right-circularly polarized light, a left-handed helix left-circularly polarized light. By altering the concentration of a chiral dopant it is possible to vary the pitch and hence the wavelength range of selectively reflected light of a chiral nematic layer. There is a direct relationship here between the reciprocal of the observed pitch p and the concentration of the chiral compound (x_{ch}):

$$1/p = HTP \ x_{ch}$$

where HTP denotes the helical twisting power of the chiral dopant.

US-A-4,637,896 discloses cholesteric liquid-crystalline compounds, based on cholesterol derivatives, and photopolymerized cholesteric coatings which comprise these compounds in copolymerized form. The cholesteric films described have reflection maxima which are predominantly within the visible wavelength range. However, two examples are also given of colorless films whose reflection maxima lie at 950 and 1260 nm respectively. Owing to the narrow breadth of reflection, however, these films are not suitable as a heat-insulating coating.

US-A-5,629,055 discloses solid cholesteric films based on cellulose. The films are obtainable from colloid suspensions of cellulose crystallites, said colloid suspensions being prepared by acidic hydrolysis of crystalline cellulose. The solid films
5 have cholesteric properties and their reflection wavelength is said to be adjustable over the entire spectral range from infrared to ultraviolet. The materials described are proposed in particular for use as optical authentication materials, since printing or photocopying techniques are unable to reproduce the
10 cholesteric effect.

US-A-5,352,312 describes a method of insulating rocket engines against heat and corrosives. The method comprises the use of an ablative insulating material which comprises a thermoplastic
15 liquid-crystalline polymer. The liquid-crystalline material, however, is not cholesteric and the insulating action is based on the ablative effect and not on the reflection of thermal radiation.

20 US-A-5,016,985 discloses an infrared filter comprising a broadband infrared filter element and a cholesteric liquid-crystalline filter element. The significance of the cholesteric filter element lies in particular in its ability to block infrared wavelengths in a precise, narrow band. The
25 infrared filter can be used, for example, in night vision equipment.

It is an object of the present invention to provide heat
30 insulation media which are easy to prepare, which are almost completely transparent in the visible range of the electromagnetic spectrum and which absorb very little in the near infrared and in the visible wavelength range of the electromagnetic spectrum.

35 We have found that this object is achieved by coatings which comprise at least one cholesteric IR-reflecting layer.

The present invention therefore provides a heat-insulating
40 coating comprising one or more cholesteric layers and reflecting at least 40%, in particular at least 45%, of the incident radiation in the infrared wavelength range, preferably above 750 nm and, in particular, in the wavelength range from 751 nm to about 2000 nm.

45

The heat-insulating coating of the invention has a series of surprising advantages:

- 5 a) incident radiation in the visible wavelength range is transmitted almost completely, so that the coating appears transparent.
- 10 b) Incident light in the infrared region of the electromagnetic spectrum is very largely reflected and not absorbed, so that the object to be insulated does not heat up through conduction.
- 15 c) There is broadband reflection of incident thermal radiation, allowing the efficient insulation of articles.
- 20 d) The thickness and uniformity of the coating can be varied within a wide range without significantly effecting its insulating properties, with the result that its preparation is considerably less complex than that, for example, of metal-containing reflective coatings.
- 25 e) The use of ecologically and toxicologically objectionable metals is avoided.
- 30 f) The starting compounds for preparing the coating are readily available industrially; their use is thus generally less expensive than that of, say, gold or silver in reflective coatings.

The heat-insulating coating of the invention preferably transmits at least 80%, in particular at least 90%, of the incident radiation in the wavelength range of visible light, i.e.
35 approximately in the range from 390 nm to 750 nm.

Particular preference is given to a heat-insulating coating of the invention which comprises two or more, preferably from about 2 to 20 and, in particular, about 2 to 10 cholesteric
40 IR-reflecting layers. With particular preference the layers have different reflection maxima in the wavelength range > 750 nm. With very particular preference the heat-insulating coating of the invention comprises two or more cholesteric layers, preferably a number of cholesteric layers which can be divided by
45 2, such as 2, 4, 6, 8 or 10, the pitch of the helical superstructures of 2 - preferably adjacent - layers in each case being identical but their handedness being different. Very

particular preference is likewise given to a heat-insulating coating of the invention which between layers having a helical superstructure of identical pitch and identical handedness has a medium which reverses the direction of rotation of the
5 transmitted circularly polarized light, especially what is known as a $\lambda/2$ film or plate.

The use of layers of different handedness, or of a medium which reverses the direction of rotation of the transmitted circularly
10 polarized light between layers of identical handedness, is able to increase considerably the reflection of the heat-insulating coating of the invention. In this way degrees of reflection of at least 75%, in particular at least 85%, based on the incident radiation are achieved preferably, in the wavelength range above
15 750 nm, in particular in the wavelength range from 751 nm to about 2000 nm.

The only restriction on the composition of the heat-insulating coating of the invention is that it must include compounds which,
20 alone or through their interaction, give it cholesteric IR-reflecting properties. In principle, virtually all known cholesteric monomers or monomer mixtures or polymers or polymer mixtures can be adjusted in the pitch of their helical
25 superstructure, by varying the chiral component, in such a way that their reflection maximum lies within the IR.

A preferred heat-insulating coating of the invention can comprise, for example, in the cured state cholesteric compounds
30 or mixtures of compounds selected from


- a) at least one cholesteric polymerizable monomer;
- b) at least one achiral, nematic, polymerizable monomer and a
35 chiral compound;
- c) at least one cholesteric crosslinkable polymer;
- d) at least one cholesteric polymer in a polymerizable diluent
40 or a mixture of polymerizable diluents;
- e) at least one cholesteric polymer whose cholesteric phase can be frozen in by rapid cooling to below the glass transition
45 temperature; or

- f) at least one achiral, liquid-crystalline crosslinkable polymer and a chiral compound.

For the purposes of the present invention, crosslinking means the covalent linking of polymeric compounds and polymerization means the covalent linking of monomeric compounds to form polymers. By curing is meant crosslinking, polymerization or the freezing-in of the cholesteric phase.

- 10 Curing fixes the uniform orientation of the cholesteric molecules in the cholesteric layer.


Preferred monomers of group a) are described in DE-A-196 02 848 and in DE-A-4 342 280, the full content of which is incorporated herein by reference. In particular, the monomers a) comprise at least one chiral, liquid-crystalline, polymerizable monomer of the formula I



where

25 Z^1 is a polymerizable group or a radical which carries a polymerizable group,

30 Y^1, Y^2, Y^3 independently are chemical bonds, oxygen, sulfur,



40 A^1 is a spacer,

M^1 is a mesogenic group,

X is an n-valent chiral radical,




45 R is hydrogen or C_1 - C_4 -alkyl,

n is 1 to 6

and the radicals Z^1 , Y^1 , Y^2 , Y^3 , A^1 and M^1 can be identical or different if n is greater than 1.

5

Preferred radicals Z^1 are:



where each R can be identical or different and is hydrogen or
 30 C_1 - C_4 -alkyl, such as methyl, ethyl, n-propyl, isopropyl, n-butyl, isobutyl, sec-butyl or tert-butyl. Of the reactive polymerizable groups, the cyanates are able to trimerize spontaneously to cyanurates and are therefore preferred. Polymerization of the
 35 other groups indicated requires further compounds having complementary reactive groups. Isocyanates, for example, are able to polymerize with alcohols to give urethanes and with amines to give urea derivatives. Similar comments apply to thiiranes and aziridines. Carboxyl groups can be condensed to give polyesters and polyamides. The maleimido group is particularly suitable for
 40 free-radical copolymerization with olefinic compounds such as styrene. Said complementary reactive groups can be present either in a second compound of the invention, which is mixed with the first, or can be incorporated into the polymeric network by means of auxiliary compounds containing 2 or more such complementary
 45 groups.

Particularly preferred groups Z^1-Y^1 are acrylate and methacrylate.

Y^1-Y^3 can be as defined above, the term chemical bond meaning a single covalent bond.

5

Suitable spacers A^1 are all groups known for this purpose. The spacers contain generally from 2 to 30, preferably from 2 to 12 carbon atoms and consist of linear aliphatic groups. They may be interrupted in the chain by nonadjacent O, S, NH or NCH_3 , for example. Other suitable substituents for the spacer chain are fluorine, chlorine, bromine, cyano, methyl and ethyl.

10

Examples of representative spacers are:

15

$-(CH_2)_p-$, $-(CH_2CH_2O)_mCH_2CH_2-$, $-CH_2CH_2SCH_2CH_2-$, $-CH_2CH_2NHCH_2CH_2-$,

20 $-CH_2CH_2N(CH_3)CH_2CH_2-$, $-(CH_2CH(CH_3)O)_mCH_2CH(CH_3)-$, $-(CH_2CH(CH_3))_6CH-$ or $-CH_2CH_2CH(Cl)-$,


where

m is 1 to 3 and

25

p is 1 to 12.

The mesogenic group M^1 preferably has the structure



30

where Y^8 is a bridge in accordance with one of the definitions of Y^1 , s is 1 to 3 and T is identical or different at each occurrence and is a divalent isocycloaliphatic, heterocycloaliphatic, isoaromatic or heteroaromatic radical. If s is >1, the bridges Y^8 can be identical or different.


35

The radicals T can also be ring systems substituted by C_1-C_4 -alkyl, C_1-C_4 -alkoxy, fluorine, chlorine, bromine, cyano, hydroxyl or nitro. Preferred radicals T are:


40

45


9




35 Particular preference is given to the following mesogenic groups
M¹:




10




5




10




15




20




25




30




35



40




45



Of the chiral radicals X of the compounds of the formula I particular preference is given, not least on account of their availability, to those derived from sugars, from binaphthyl or biphenyl derivatives and from optically active glycols, dialcohols or amino acids. In the case of the sugars, particular mention should be made of pentoses and hexoses and derivatives thereof.

Examples of radicals X are the following structures, the lines at the end in each case denoting the free valences.





35



40

45





5






10





15







20







25







30



35




40




45

13

5




10




15



20



25




30

35


40

45

14




25 Particular preference is given to



40 Also suitable, furthermore, are chiral groups having the following structures:

45

15




Further examples are set out in the German Application
P 43 42 280.2.

15 n is preferably 2.

Preferred monomers of group a), furthermore, are chiral
polymerizable cholesterol derivatives as are described in
20 DE-A-35 35 547 and in US-A-4,637,896, the full content of which
is incorporated herein by reference.

Examples of preferred monomers of group b) are described in the
dissertation by H. Jonsson, Department of Polymer Technology,
25 Royal Institute of Technology, S-10044 Stockholm, Sweden, of
Jan. 25, 1991, in DE-A-4 408 171, DE-A-4 408 170 and DE-A-4 405
316, the full content of which is incorporated herein by
reference. The cholesteric mixture preferably comprises at least
one achiral liquid-crystalline polymerizable monomer of the
30 formula II



35


where

40 Z^2, Z^3 are identical or different polymerizable groups or
radicals which contain a polymerizable group,

n is 0 or 1

45 Y^4, Y^5, Y^6, Y^7 independently are chemical bonds, oxygen, sulfur,

16



5

A^2, A^3 are identical or different spacers and

10

M^2 is a mesogenic group.

The polymerizable groups, the bridges Y^4 to Y^7 , the spacers and the mesogenic group are subject to the same preferences as the corresponding variables of the formula I.


15

In addition, the mixture of group b) includes a chiral compound. The chiral compound brings about the twisting of the achiral liquid-crystalline phase to form a cholesteric phase. In this context, the extent of twisting depends on the twisting power of the chiral dopant and on its concentration. Consequently, therefore, the pitch of the helix and, in turn, the reflection wavelength depend on the concentration of the chiral dopant. As a result, it is not possible to indicate a generally valid concentration range for the dopant. The dopant is added in the amount at which the desired reflection is produced.

25

Preferred chiral compounds are those of the formula Ia

30



35

where Z^1 , Y^1 , Y^2 , Y^3 , A^1 , X and n are as defined above and M^a is a divalent radical which comprises at least one heterocyclic or isocyclic ring system.

40

The moiety M^a here resembles the mesogenic groups described, since in this way a particularly good compatibility with the liquid-crystalline compound is achieved. M^a , however, need not be mesogenic, since the compound Ia is intended to bring about an appropriate twisting of the liquid-crystalline phase merely by virtue of its chiral structure. Preferred ring systems present in M^a are the abovementioned structures T, preferred structures M^a being those of the abovementioned formula $(T-Y^8)_s-T$. Further monomers and chiral compounds of group b) are described in

45

WO 97/00600 and its parent DE-A-195 324 08, the full content of which is incorporated herein by reference.

Preferred polymers of group c) are cholesteric cellulose
5 derivatives as described in DE-A-197 136 38, especially
cholesteric mixed esters of

- (VI) hydroxyalkyl ethers of cellulose with
- 10 (VII) saturated, aliphatic or aromatic carboxylic acids and
- (VIII) unsaturated mono- or dicarboxylic acids.

Particular preference is given to mixed esters in which the
hydroxyalkyl radicals of component VI that are attached by way of
15 ether functions comprise straight-chain or branched
C₂-C₁₀-hydroxyalkyl radicals, especially hydroxypropyl and/or
hydroxyethyl radicals. Component VI of the suitable mixed esters
preferably has a molecular weight of from about 500 to about 1
million. Preferably, the anhydroglucose units of the cellulose
20 are etherified with hydroxyalkyl radicals in an average molar
degree of substitution of from 2 to 4. The hydroxyalkyl groups in
the cellulose can be identical or different. Up to 50% of them
can also be replaced by alkyl groups (especially C₁-C₁₀-alkyl
groups). One example of such a compound is hydroxypropyl-
25 methylcellulose.

Compounds which can be used as component VII of the mixed esters
that are employable are straight-chain aliphatic C₁-C₁₀ carboxylic
acids, especially C₂-C₆ carboxylic acids, branched aliphatic
30 C₄-C₁₀ carboxylic acids, especially C₄-C₆ carboxylic acids, or
straight-chain or branched halocarboxylic acids. Component VII
can also comprise benzoic acid or aliphatic carboxylic acids with
aromatic substituents, especially phenylacetic acid. Component
35 VII is selected with particular preference from acetic,
propionic, n-butyric, isobutyric and n-valeric acid, in
particular from propionic, 3-chloropropionic, n-butyric and
isobutyric acid.

40 Component VIII is preferably selected from unsaturated C₃-C₁₂
mono- or dicarboxylic acids or monoesters of such a dicarboxylic
acid, especially α,β -ethylenically unsaturated C₃-C₆ mono- or
dicarboxylic acids or monoesters of the dicarboxylic acids.

With particular preference, component VIII of the employable mixed esters is selected from acrylic, methacrylic, crotonic, vinylacetic, maleic, fumaric and undecenoic acid, especially from acrylic and methacrylic acid.

5

Component VI is preferably esterified with component VII and VIII in an average degree of molar substitution of from 1.5 to 3, in particular from 1.6 to 2.7 and, with particular preference, from 2.3 to 2.6. Preferably about 1 to 30%, in particular from 1 to 20% or 1 to 10%, with particular preference from about 5 to 7%, of the OH groups of component VI are esterified with component VIII.

10

The proportion of component VII to component VIII determines the reflection wavelength of the polymer.


15

Highly suitable polymers of group c), moreover, are the propargyl-terminated cholesteric polyesters or polycarbonates described in DE-A-197 17 371.


20

Among these compounds, preference is given to polyesters or polycarbonates having at least one propargyl end group of the formula $R^3C\equiv C-CH_2-$, where R^3 is H, C_1-C_4 -alkyl, aryl or Ar- C_1-C_4 -alkyl (e.g. benzyl or phenethyl) which is attached to the polyesters or polycarbonates directly or via a linker. The linker is preferably selected from

25



30




(the propargyl group is attached to X),

35

where R^4 is H, C_1-C_4 -alkyl or phenyl, X is O, S or NR^2 and R^2 is H, C_1-C_4 -alkyl or phenyl.

40

In the polyesters the propargyl end group is preferably attached via



45


The polyesters preferably comprise

(IX) at least one aromatic or araliphatic dicarboxylic acid unit
and/or at least one aromatic or araliphatic hydroxy
5 carboxylic acid unit and

(X) at least one diol unit.


Preferred dicarboxylic acid units are those of the formula

10




15


20



25




30




especially those of the formula

35



40



45

20

it being possible for each of the phenyl groups, or the naphthyl group, to contain 1, 2 or 3 substituents selected independently of one another from C₁-C₄-alkyl, C₁-C₄-alkoxy, halogen and phenyl and where, in the above formulae,

5

W is NR, S, O, (CH₂)_pO(CH₂)_q, (CH₂)_m or a single bond,



R is alkyl or hydrogen,

m is an integer from 1 to 15 and

10 p and q independently are integers from 0 to 10.

Preferred hydroxy carboxylic acid units are those of the formula

15




20

where each phenyl group or the naphthyl group can have 1, 2 or 3 substituents selected independently of one another from C₁-C₄-alkyl, C₁-C₄-alkoxy, halogen and phenyl.

25

Preferred diol units are those of the formula

30




35


40

45


5





10





15





20





25



30




35



40

especially those of the formula

45




20 where, in the above formulae,


L is alkyl, alkoxy, halogen, COOR, OCOR, CONHR or NHCOR,

X is S, O, N, CH₂ or a single bond,

25 A is a single bond, (CH₂)_n, O(CH₂)_n, S(CH₂)_n, NR(CH₂)_n,



30



35

R is alkyl or hydrogen,


R¹ is hydrogen, halogen, alkyl or phenyl and

n is an integer from 1 to 15.


40 Preference is given to polyesters comprising at least one dicarboxylic acid unit of the formula

45

23




5



and at least one diol unit of the formula

10




15

H, halogen, C₁-C₄-alkyl, especially CH₃ or C(CH₃)₃, or phenyl.

Further preferred compounds are diesters of the formula

20 P-Y-B-CO-O-A-O-CO-B-Y-P, where P is a propargyl end group of the above-defined formula, Y is O, S or NR² (R² = C₁-C₄-alkyl), B is




25

where each phenyl group or the naphthyl group can have 1, 2 or 3 substituents selected independently of one another from C₁-C₄-alkyl, C₁-C₄-alkoxy, halogen and phenyl, and A (together with the adjacent oxygen atoms) is one of the abovementioned diol units.

30


Particularly preferred diesters are those of the abovementioned formula in which B is

35




and especially diesters of the formula

40




45


24

(XI) B is  and


5



10



15


(XII) B is  and

A is as defined for XI.

20


Further preferred compounds are polycarbonates comprising at least one incorporated diol unit of the abovementioned formulae, especially of the formulae

25




or

30



Preference is given here to those polycarbonates which comprise as diol units at least one mesogenic unit of the formula




40

at least one chiral unit of the formula


45

25

5




or



with or without a non-chiral unit of the formula


10



15 R^1 being as defined above and in particular being H or CH_3 .


Particularly preferred polycarbonates are those having propargyl end groups of the formula $HC\equiv CCH_2O-R^5-CO$, where R^5 is

20



Further suitable polymers of group c) are cholesteric polycarbonates containing photoreactive groups even in a non-terminal position. Such polycarbonates are described in DE-A-196 31 658 and are preferably of the formula XIII

30




(XIII)

35 where the molar ratio $w/x/y/z$ is from about 1 to 20/from about 1 to 5/from about 0 to 10/from about 0 to 10, particularly preferably from about 1 to 5/from about 1 to 2/from about 0 to 5/from about 0 to 5.

40 In the formula XIII


A is a mesogenic group of the formula

45




26

B is a chiral group of the formula




D is a photoreactive group of the formula

27



5

or




10

and

E is a further, non-chiral group of the formula

15




20

where, in the above formulae,

L is alkyl, alkoxy, halogen, COOR, OCOR, CONHR or NHCOR,


X is S, O, N, CH₂ or a single bond,

25 R is alkyl or hydrogen,

A is a single bond, (CH₂)_n, O(CH₂)_n, S(Cu₂)_n, NR(CH₂)_n,

30


or



35


R¹ is hydrogen, halogen, alkyl or phenyl and

n is an integer from 1 to 15.

40 If R¹ is alkyl or halogen and A is a single bond, or if R¹ is H or alkyl and A is

45

the groups are solubility-improving groups. Examples thereof are




5

Isosorbide, isomannide and/or isoidide is the preferred chiral component.


- 10 The proportion of the chiral diol structural units is preferably within the range from 1 to 80 mol-% of the overall content of diol structural units, with particular preference from 2 to 20 mol-%, depending on the desired reflection behavior.

- 15 Examples of preferred polymers of group d) are crosslinkable cholesteric copolyisocyanates as described in US-A-08 834 745, the full content of which is incorporated herein by reference. Such copolyisocyanates have repeating units of the formulae

20




25



30

and, if appropriate, of the formula

35



where

40

R¹ is a chiral aliphatic or aromatic radical,

R² is a crosslinkable radical and

45

R³ is an achiral radical.

Unless specified otherwise alkyl here (including definitions such as alkoxy, dialkyl, alkylthio, etc.) means a branched or unbranched C₁-C₁₂-alkyl, preferably C₃-C₁₂-alkyl, with particular preference C₄-C₁₀-alkyl and, in particular, C₆-C₁₀-alkyl.

5

R¹ is selected preferably from (chiral) branched or unbranched alkyl, alkoxyalkyl, alkylthioalkyl, cycloalkyl, alkylphenyl or C₃-C₉-epoxyalkyl radicals or radicals of esters of C₁-C₆ fatty acids with C₁-C₆-alkanols or C₃-C₉-dialkyl ketones. The ester radical can be attached to the nitrogen either by way of the fatty acid component or by way of the alkanol radical. The radical R¹ can have 1, 2 or 3 substituents which are identical or different and are selected from alkoxy, di-C₁-C₄-alkylamino, CN, halogen or C₁-C₄-alkylthio groups.




15



R¹ is preferably selected from alkyl, alkoxyalkyl, radicals of esters of C₁-C₆ fatty acids with C₁-C₆-alkanols, C₃-C₉-dialkyl ketones and epoxidized C₃-C₉-epoxyalkyl radicals, where R¹ can be substituted by 1 or 2 radicals which are identical or different and are selected from alkoxy, halogen, CN and CF₃. Preferred substituents of branched or unbranched alkyl or alkoxy radicals are selected from alkoxy groups, halogen atoms or CN; for esters of C₁-C₆ fatty acids with C₁-C₆-alkanols, from alkoxy groups, halogen atoms, CN and CF₃, and for C₃-C₉-dialkyl ketones from alkoxy groups, halogen atoms and CN.

25



The main chain of the radical R¹ has a length in particular of from 3 to 12, especially from 6 to 10 and, preferably, from 6 to 8 members (carbons, oxygens and/or sulfur atoms). Particular preference is given to radicals R¹ selected from

30









5





10





15





20





25




30




35




40



45



5



10

With very particular preference, component III of the copolyisocyanates that can be employed is derived from 2,6-dimethylheptyl isocyanate.

15

The radical R^2 of the copolyisocyanates that can be employed is preferably selected from C_3 - C_{11} -alkenyl radicals, C_4 - C_{11} -vinyl ether radicles (= vinyl C_2 - C_9 -alkyl ethers), ethylenically unsaturated C_3 - C_{11} carboxylic acid radicals and esters of

20

ethylenically unsaturated C_3 - C_6 monocarboxylic acids with C_2 - C_6 -alkanols, the bond to the nitrogen atom being by way of the alcohol radical of the ester. With particular preference the radical is selected from methyl, ethyl, propyl, n-butyl, isobutyl and 2-ethylhexyl acrylate and from methyl, ethyl, propyl,

25

n-butyl, isobutyl and 2-ethylhexyl methacrylate, in particular from ethyl acrylate and ethyl methacrylate.

The radical R^3 preferably has the same meanings as the radical R^1 . However, it is achiral - in other words, it has no center of

30

chirality, or is present as a racemic mixture.

With particular preference, the main chain of the radical R^3 has a length from 4 to 12, in particular from 6 to 10 and, preferably, from 6 to 8 members (carbon, oxygen and/or sulfur atoms). With

35

very particular preference, component V of the copolyisocyanates of the invention is derived from n-hexyl, n-heptyl or n-octyl isocyanate.

40

Components III, IV and V are preferably present in a molar ratio III:IV:V of from about 1 to 20 : 1 to 20 : 50 to 98, in particular from about 5 to 15 : 5 to 15 : 65 to 90 and, with particular preference, about 15:10:75.

45

The units III, IV and V can be in random distribution within the copolyisocyanates that can be employed.

32

Suitable polymers of group e) are chiral nematic polyesters having flexible chains, which comprise isosorbide, isomannide and/or isoidide units, preferably isosorbide units, and for chain flexibilization comprise at least one unit selected from (and 5 derived from)


- (a) aliphatic dicarboxylic acids,
- (b) aromatic dicarboxylic acids with a flexible spacer,
- 10 (c) α,ω -alkanediols,
- (d) diphenols with a flexible spacer and
- (e) condensation products of a polyalkylene terephthalate or polyalkylene naphthalate with an acylated diphenol and an acylated isosorbide,

15

as are described in DE-A-197 04 506.

The polyesters are noncrystalline and form stable cholesteric 20 phases which can be frozen in on cooling to below the glass transition temperature. The glass transition temperatures of the polyesters, in turn, despite the flexibilization are above 80°C, preferably above 90°C and, in particular, above 100°C.


25 The polyesters that can be employed include as units (a) preferably those of the formula



30

where n is 3 to 15, especially 4 to 12, and with particular preference adipic acid;

35 as units (b) preferably those of the formula



40

where

A is $(\text{CH}_2)_n$, $\text{O}(\text{CH}_2)_n\text{O}$ or $(\text{CH}_2)_o\text{---O---}(\text{CH}_2)_p$,


45

33

n is 3 to 15, especially 4 to 12 and, with particular preference, 4 to 10, and

5 o and p independently are from 1 to 7;

as units (c) preferably those of the formula




where

15 n is 3 to 15, especially 4 to 12 and, with particular preference, 4 to 10, and

m is 1 to 10; and

as units (d) preferably those of the formula

20



25

where

30 A is $(\text{CH}_2)_n$, $\text{O}(\text{CH}_2)_n\text{O}$ or $(\text{CH}_2)_o\text{---O---}(\text{CH}_2)_p$,

n is 3 to 15, especially 4 to 12 and, with particular preference, 4 to 10, and


35 o and p independently are 1 to 7.

The polyesters that can be employed comprise additionally, as nonflexible acid component, preferably dicarboxylic acid units of the formula

40


45

34





and as nonflexible alcohol component diol units of the formula

35





45


35



10



20





30 where, in the above formulae,

L is alkyl, alkoxy, halogen, COOR, OCOR, CONHR or NHCOR,

35 X is S, O, N, CH₂ or a single bond,

A is a single bond,



45




where

36

R^1 is hydrogen, halogen, alkyl or phenyl and

R is alkyl or hydrogen.

- 5 The polyesters that can be employed may include additional flexible diol units of the formula




R^1 is hydrogen, halogen, alkyl or phenyl,

- 25 A is $(\text{CH}_2)_n$, $\text{O}(\text{CH}_2)_n$, $\text{S}(\text{CH}_2)_n$ or $\text{NR}(\text{CH}_2)_n$, and

n is 1 to 15.


- 30 Examples of preferred polymers of group f) are crosslinkable liquid-crystalline polyorganosiloxanes as are described in EP-A-066 137 and in EP-A-358 208. The mixture of group f) additionally comprises a chiral compound. Suitable chiral compounds are, in particular, the chiral dopants of the formula Ia described for the mixtures of group b).

- 35 With very particular preference, the heat-insulating coating of the invention comprises chiral compounds and nematic monomers of group b), especially chiral compounds of the formula 2:




- 45 and/or of the formula 5:


37




10 and nematic monomers of the formula 1:



20 of the formula 3:



30 or of the formula 4:



40 in the cured state, where n_1 and n_2 in the formulae 1 and 3 are independently 2, 4 or 6 and the monomers of the formula 1 or 3 are preferably employed as mixtures of compounds with $n_1/n_2 = 2/4, 2/6, 4/2, 6/2, 4/4, 4/6, 6/4$ or $6/6$, and R in formula 4 is H, Cl or CH_3 .

45 The present invention additionally provides a process for producing a heat-insulating coating, which comprises applying to a transparent substrate at least one cholesteric IR-reflecting

layer, curing it, applying, if desired, one or more further cholesteric IR-reflecting layers and, if desired, a medium which reverses the direction of rotation of the transmitted circularly polarized light, curing said layer(s) and so completing the
5 heat-insulating coating.

The transparent substrate to which the IR-reflecting layer(s) is(are) applied can be, for example, a glazed unit, a window pane or a film which is to be bonded adhesively to a window pane for
10 insulation purposes.

The cholesteric IR-reflecting layer can be applied to the substrate by customary techniques: for example, by means of techniques selected from air knife coating, bar coating, squeeze
15 coating, impregnating, reverse roll coating, transfer roll coating, gravure coating, kiss coating, casting, spraying, spin coating or printing techniques, such as letterpress, flexographic, intaglio, offset or screen printing.

The IR-reflecting layer(s) can be applied in the form of low-gap or high-viscosity mixtures to the substrate, but preferably as low-viscosity mixtures. To this end the cholesteric mixtures can be applied to the substrate in undiluted or minimally diluted
20 form at an elevated temperature or in highly diluted form at a low temperature.

The cholesteric mixtures and the formulations comprising absorption pigments can be diluted with any suitable diluent
25 prior to their application to the substrate.

Examples of diluents which can be employed in the process of the invention for the compounds of groups a) or b) are linear or branched esters, especially acetic esters, cyclic ethers and
35 esters, alcohols, lactones, aliphatic and aromatic hydrocarbons, such as toluene, xylene and cyclohexane, and also ketones, amides, N-alkylpyrrolidones, especially N-methylpyrrolidone, and, in particular, tetrahydrofuran (THF), dioxane and methyl ethyl ketone (MEK).
40

Examples of suitable diluents for the polymers of group c) are ethers and cyclic ethers such as tetrahydrofuran or dioxane, chlorinated hydrocarbons such as dichloromethane,
45 1,1,2,2-tetrachloroethane, 1-chloronaphthalene, chlorobenzene or 1,2-dichlorobenzene. These diluents are particularly suitable for polyesters and polycarbonates. Examples of suitable diluents for cellulose derivatives are ethers, such as dioxane, or ketones,

such as acetone. Where copolyisocyanates are employed as polymers of group d) it is advisable to use polymerizable diluents as described in US-A-08 834 745. Examples of such polymerizable diluents are

- 5
- esters of α, β -unsaturated mono- or dicarboxylic acids, especially C_3 - C_6 mono- or dicarboxylic acids, with C_1 - C_{12} -alkanols, C_2 - C_{12} -alkanediols or their C_1 - C_6 -alkyl ethers and phenyl ethers, examples being acrylates and
 - 10 methacrylates, hydroxyethyl or hydroxypropyl acrylate or methacrylate, and 2-ethoxyethyl acrylate or methacrylate;
 - vinyl C_1 - C_{12} -alkyl ethers, such as vinyl ethyl, hexyl or octyl
 - 15 ether;
 - vinyl esters of C_1 - C_{12} carboxylic acids, such as vinyl acetate, propionate or laurate;
 - 20 - C_3 - C_9 epoxides, such as 1,2-butylene oxide, styrene oxide;
 - N-vinylpyrrolidone, N-vinylcaprolactam, N-vinylformamide;
 - 25 - vinylaromatic compounds, such as styrene, α -methylstyrene, chlorostyrene, and
 - compounds having two or more crosslinkable groups, such as diesters of diols (including polyethylene glycols) with
 - 30 acrylic or methacrylic acid or divinylbenzene.

Examples of preferred polymerizable diluents are 2-ethoxyethyl acrylate, diethylene glycol diacrylate, ethylene glycol dimethacrylate, diethylene glycol dimethacrylate, triethylene

35 glycol dimethacrylate, diethylene glycol monomethyl ether acrylate, phenoxyethyl acrylate and tetraethylene glycol dimethacrylate. A particularly preferred polymerizable diluent is styrene.

- 40 The mixtures of groups a), b) or c) may also include polymerizable diluents in small amounts. Preferred polymerizable solvents which can be added to a), b) or c) are acrylates, especially acrylates of relatively high functionality such as bis-, tris- or tetraacrylates and, with particular preference,
- 45 high-boiling oligoacrylates. The preferred amount added is

approximately 5% by weight, based on the overall weight of the mixture.

- For photochemical polymerization, the cholesteric mixture may
- 5 include customary commercial photoinitiators. For curing by electron beams, such initiators are not required. Examples of suitable photoinitiators are isobutyl benzoin ether, 2,4,6-trimethylbenzoyldiphenylphosphine oxide, 1-hydroxycyclohexyl phenyl ketone,
 - 10 2-benzyl-2-dimethylamino-1-(4-morpholinophenyl)-furan-1-one, mixtures of benzophenone and 1-hydroxycyclohexyl phenyl ketone, 2,2-dimethoxy-2-phenylacetophenone, perfluorinated diphenyltitanocenes, 2-methyl-1-(4-[methylthio]phenyl)-2-(4-morpholinyl)-1-propanone,
 - 15 2-hydroxy-2-methyl-1-phenylpropan-1-one, 4-(2-hydroxyethoxy)phenyl 2-hydroxy-2-propyl ketone, 2,2-diethoxyacetophenone, 4-benzoyl-4'-methyldiphenyl sulfide, ethyl 4-(dimethylamino)benzoate, mixtures of 2-isopropylthioxanthone and 4-isopropylthioxanthone,
 - 20 2-(dimethylamino)ethyl benzoate, d,l-camphorquinone, ethyl-d,l-camphorquinone, mixtures of benzophenone and 4-methylbenzophenone, benzophenone, 4,4'-bisdimethylaminebenzophenone, (η^5 -cyclopentadienyl)(η^6 -isopropylphenyl)iron(II)
 - 25 hexafluorophosphate, triphenylsulfonium hexafluorophosphate or mixtures of triphenylsulfonium salts, and butanediol diacrylate, dipropylene glycol diacrylate, hexanediol diacrylate, 4-(1,1-dimethylethyl)cyclohexyl acrylate, trimethylolpropane triacrylate and tripropylene glycol diacrylate.

30

In order to adjust the viscosity and the leveling behavior it is possible for the cholesteric mixtures to be mixed with additional components.

35

For example, it is possible to employ polymeric binders and/or monomeric compounds which can be converted into a polymeric binder by polymerization. Examples of suitable such compounds are organic-solvent-soluble polyesters, cellulose esters,

- 40 polyurethanes and silicones, including polyether- or polyester-modified silicones. It is particularly preferred to employ cellulose esters such as cellulose acetobutyrate.

45

The addition of small amounts of suitable leveling agents may also be advantageous. It is possible to employ from about 0.005 to 1% by weight, in particular from 0.01 to 0.5% by weight, based on the amount of cholesteric employed. Examples of suitable

leveling agents are glycols, silicone oils and, in particular, acrylate polymers, such as the acrylate copolymers obtainable under the name Byk 361 or Byk 358 from Byk-Chemie and the modified, silicone-free acrylate polymers obtainable under the
5 name Tego flow ZFS 460 from Tego.

The cholesteric mixture may also include stabilizers to counter the effects of UV and weather. Examples of suitable such additives are derivatives of 2,4-dihydroxybenzophenone,
10 derivatives of 2-cyano-3,3-diphenyl acrylate, derivatives of 2,2',4,4'-tetrahydroxybenzophenone, derivatives of ortho-hydroxyphenylbenzotriazole, salicylic esters, ortho-hydroxyphenyl-s-triazines or sterically hindered amines. These substances can be employed alone or, preferably, as
15 mixtures.

The IR-reflecting layer(s) applied can be cured thermally, photochemically or by a beam of electrons.

20 Curing must of course take place in the cholesteric phase and with retention of the cholesteric phase.

Where two or more layers are applied, they can in each case be
25 applied, dried - if desired - and cured individually. However, it is likewise possible to apply two or more, or all, of the layers to be applied in one application procedure, wet-on-wet, to the article that is to be coated, to carry out conjoint drying if desired and then to carry out conjoint curing. A prerequisite for
30 the simultaneous application of the cholesteric layers, however, is that there is no interdiffusion between different layers having a different reflection behavior.

Casting techniques are particularly suitable for the
35 simultaneous application of cholesteric layers, especially knife or bar casting techniques, cast-film extrusion or stripper casting techniques, and the cascade casting process. These casting techniques are described, for example, in DE-A-19 504 930, EP-A-431 630, DE-A-3 733 031 and EP-A-452 959,
40 which are expressly incorporated herein by reference.

The present invention additionally provides a multicomponent coating system comprising components which are capable of forming
45 cholesteric layers having mutually different reflection maxima in the wavelength range > 750 nm. By means of such a coating system of the invention, whose components can be employed, for example,

as coating formulations, it is possible to provide any desired substrate with a heat-insulating coating of the invention.

5 The heat-insulating coating of the invention is particularly suitable for producing insulated windows or heat-insulating transparent construction materials, or for insulating residential, office or industrial buildings against thermal radiation. In addition, the heat-insulating coating of the invention is also particularly suitable for use in the automotive
10 sector, especially for producing heat-insulating laminated glass screens. Its use for these purposes is therefore also provided for by the present invention.

15 The Examples which follow illustrate the invention without limiting it to them.

Examples 1 to 3 used a nematic liquid-crystalline mixture of the formula 1 which is present up to 5°C in the smectic phase, up to
20 68°C in the nematic phase and above 68°C in the isotropic phase (S 5 N 68 I).

The chiral dopant employed in Examples 1 and 2 was the compound of the formula 2 and in Example 3 the compound of the formula 5.
25

Cellulose acetobutyrate in a concentration of 0.8% by weight based on the cholesteric mixture was added to the mixtures employed in Examples 1 to 3 in order to improve layering, and the overall mixture was dissolved in butyl acetate.
30 2,4,6-Trimethylbenzoyldiphenylphosphine oxide as photoinitiator was added in a concentration of 1.5% by weight, based on the cholesteric mixture. This mixture was applied with a doctor blade in a wet-film thickness of 30 µm to a glass plate. In all three examples, a homogeneous transparent layer was formed in each case
35 following the evaporation of the solvent. This layer was crosslinked photochemically using a UV light source.

40 Example 1:

Five cholesteric layers were each applied individually and cured as described above. The compositions of the cholesteric layers differed in terms of the concentration of the ingredients, as
45 shown in the following Table 1:

Layer	x_{ch}	x_n	λ_R
1	0.032	0.968	220
2	0.027	0.973	943
3	0.024	0.976	1085
4	0.021	0.979	1250
5	0.018	0.982	1440

In addition, all layers contained cellulose acetobutyrate and 2,4,6-trimethylbenzoyldiphenylphosphine oxide in the amounts indicated above.

The concentration of the chiral component is abbreviated to x_{ch} and is indicated as a molar fraction. The concentration of the nematic component is abbreviated to x_n and likewise indicated as a molar fraction. λ_R indicates the wavelength of the reflection maximum in nm.

The layers applied atop one another gave a reflection of 47% of the incident light in the wavelength range between 752 and 1500 nm. The transparency in the visible wavelength range (between 400 and 700 nm) was more than 95%.

Example 2:

Example 2 was carried out using the mixture present in layer 1 of Example 1. As indicated above this mixture was applied to two glass plates with a doctor blade which applies a wet-film thickness of 30 μm , the solvent was stripped off, and the resulting transparent film was cured photochemically by means of a UV light source (Nitraphot lamp from OSRAM). Then a $\lambda/2$ film (from Nitto) was placed between the coated glass plates in such a way that the liquid-crystalline layers were in contact with the $\lambda/2$ film. The optical behavior of this arrangement was examined spectroscopically. It was found that the coating comprising the $\lambda/2$ film had a degree of reflection of 89% in the wavelength range from 752 to 880 nm and a transmission in the visible wavelength range of more than 93%.

Example 3:

Using a doctor blade, two layers were applied individually atop one another in succession with a wet-film thickness of in each case 30 μm , the solvent was stripped off and the resulting film, which is about 16 μm thick and is transparent in the visible range, was cured photochemically with the light source indicated

above. The two overlying layers were identical in their material composition; they both contained 13 molar parts of cholesteric to 87 molar parts of the nematic compound as well as cellulose acetobutyrate and 2,4,6-trimethylbenzoyldiphenylphosphine oxide in the amounts indicated above. The wavelength of the reflection maximum for both layers was 820 nm. The layers differed, however, in their handedness; the helical structure of one layer was right-handed, that of the other layer left-handed. Spectroscopic investigations showed a selective reflection of 94% at a wavelength of 820 nm. The mid-peak width of the reflection was 121 nm. The transmission in the visible wavelength range was more than 93%.

15

411/cb

20

25

30

35

40

45

We claim:

- 5 1. A heat-insulating coating comprising one or more cholesteric layers and reflecting at least 40%, in particular at least 45%, of the incident radiation in the infrared wavelength range, preferably above 750 nm and, in particular, in the wavelength range from 751 nm to about 2000 nm.
- 10 2. A heat-insulating coating as claimed in claim 1, which transmits at least 80%, in particular at least 90%, of the incident radiation in the wavelength range from about 390 nm to 750 nm.
- 15 3. A heat-insulating coating as claimed in either of the preceding claims, which comprises two or more, preferably from about 2 to 20, and, in particular, from about 2 to 10 cholesteric IR-reflecting layers.
- 20 4. A heat-insulating coating as claimed in claim 3, whose cholesteric layers have mutually different reflection maxima in the wavelength range > 750 nm.
- 25 5. A heat-insulating coating as claimed in any of the preceding claims, which comprises two or more cholesteric layers, preferably a number of cholesteric layers which can be divided by 2, the pitch of the helical superstructures of 2 layers in each case being identical but their handedness
30 being different.
- 35 6. A heat-insulating coating as claimed in any of the preceding claims which between layers having a helical superstructure of identical pitch and identical handedness has a medium which reverses the direction of rotation of the transmitted circularly polarized light, especially what is known as a $\lambda/2$ film or plate.
- 40 7. A heat-insulating coating as claimed in claim 6 which reflects at least 75%, in particular at least 85%, of the incident radiation in the wavelength range above 750 nm, in particular in the wavelength range from 751 nm to about 2000 nm.

46

8. A heat-insulating coating as claimed in any of the preceding claims, which in the cured state comprises cholesteric compounds or mixtures of compounds selected from
- 5 a) at least one cholesteric polymerizable monomer;
 - b) at least one achiral, nematic, polymerizable monomer and a chiral compound;
 - 10 c) at least one cholesteric crosslinkable polymer;
 - d) at least one cholesteric polymer in a polymerizable diluent or a mixture of polymerizable diluents;
 - 15 e) at least one cholesteric polymer whose cholesteric phase can be frozen in by rapid cooling to below the glass transition temperature; or
 - 20 f) at least one achiral, liquid-crystalline crosslinkable polymer and a chiral compound.
9. A process for producing a heat-insulating coating as claimed in any of the preceding claims, which comprises applying to a transparent substrate at least one cholesteric IR-reflecting layer, curing it, applying, if desired, one or more further cholesteric IR-reflecting layers and, if desired, a medium which reverses the direction of rotation of the transmitted circularly polarized light, curing said layer(s) and so completing the heat-insulating coating.
10. A multicomponent coating system comprising components capable of forming cholesteric layers in accordance with the definition in any of claims 4 to 8.
11. The use of a heat-insulating coating as claimed in any of claims 1 to 8 for producing insulating windows or heat-insulating transparent construction materials or for insulating residential, office or industrial buildings.
12. The use of a heat-insulating coating as claimed in any of claims 1 to 8 in the automotive sector, especially for producing heat-insulating laminated glass screens.

47

13. A film, in particular an adhesive film, comprising a heat-insulating coating as claimed in any of claims 1 to 8.

5

10

15

20

25

30

35

40

45

Abstract

5 The invention relates to a heat-insulating coating which
comprises one or more cholesteric IR-reflecting layers and to
processes for its preparation and to its use.

10

15

20

25

30

35

40

45

Declaration, Power of Attorney

(12)

Page 1 of 4

0050/048448

We (I), the undersigned inventor(s), hereby declare(s) that:

My residence, post office address and citizenship are as stated below next to my name,

We (I) believe that we are (I am) the original, first, and joint (sole) inventor(s) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Heat-insulating coating

the specification of which

☐ is attached hereto.

☐ was filed on _____ as

Application Serial No. _____

and amended on _____.

☒ was filed as PCT international application

Number PCT/EP 98/06527

on October 14, 1998

and was amended under PCT Article 19

on _____ (if applicable).

We (I) hereby state that we (I) have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

We (I) acknowledge the duty to disclose information known to be material to the patentability of this application as defined in Section 1.56 of Title 37 Code of Federal Regulations.

We (I) hereby claim foreign priority benefits under 35 U.S.C. § 119(a)–(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed. Prior Foreign Application(s)

Application No.	Country	Day/Month/Year	Priority Claimed
19745647.2	Germany	15 October 1997	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

We (I) hereby claim the benefit under Title 35, United States Codes, § 119(e) of any United States provisional application(s) listed below.

(Application Number)

(Filing Date)

(Application Number)

(Filing Date)

We (I) hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

Application Serial No.

Filing Date

Status (pending, patented,
abandoned)

_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

And we (I) hereby appoint:

Norman F. Oblon, Registration Number 24, 618;
 Marvin J. Spivak, Registration Number 24, 913;
 Gregory J. Maier, Registration Number 25, 599;
 William E. Beaumont, Registration Number 30, 996;
 Steven B. Kelber, Registration Number 30, 073;
 Jean-Paul Lavalleye, Registration Number 31, 451;
 Timothy R. Schwartz, Registration Number 32, 171;
 Stephen G. Baxter, Registration Number 32, 884;
 Richard L. Treanor, Registration Number 36, 379;
 Robert W. Hahl, Registration Number 33, 893;

our (my) attorneys, with full powers of substitution and revocation, to prosecute this application and to transact all business in the Patent Office connected therewith; and we (I) hereby request that all correspondence regarding this application be sent to the firm of **OBLON, SPIVAK, McCLELLAND, MAIER & NEUSTADT, P. C.**, whose Post Office Address is: **Fourth Floor, 1755 Jefferson Davis Highway, Arlington, Virginia 22202.**

We (I) declare that all statements made herein of our (my) own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

1 - 00 Karl Siemensmeyer
NAME OF INVENTOR

Karl Siemensmeyer
Signature of Inventor

Date February 14, 2000

Erich-Heckel-Str.1
67227 Frankenthal DEX
Germany
Citizen of: Germany
Post Office Address: same as residence

2 - 00 Peter Schuhmacher
NAME OF INVENTOR

Peter Schuhmacher
Signature of Inventor

Date February 14, 2000

Waldparkdamm 6
68163 Mannheim DEX
Germany
Citizen of: Germany
Post Office Address: same as residence

3 - 00 Frank Meyer
NAME OF INVENTOR

Frank Meyer
Signature of Inventor

Date February 14, 2000

Seckenheimer Str. 4-6
68165 Mannheim DEX
Germany
Citizen of: Germany
Post Office Address: same as residence

4 - 00 Norbert Schneider
NAME OF INVENTOR

Norbert Schneider
Signature of Inventor

Date February 14, 2000


Madenburgstr.5f
67122 Altrip DEX
Germany
Citizen of: Germany
Post Office Address: same as residence

Declaration

Page 4 of 4

0050/048448

Hiroki Ishida
NAME OF INVENTOR


Signature of Inventor

Date February 14, 2000

Weinstr. 93
67434 Neustadt D E X
Germany
Citizen of: Turkey
Post Office Address: same as residence